

7-bit character enable odd verify

ComPortSpeed: 2400

Data	xxxx B	xxxx B						
0	0011	LCD(1)	0-4					
1	0011	LCD(2)	0-9					
2	0011	LCD(3)	0-9					
3	0011	LCD(4)	0-9					
4	0011	LCD(5)	0-9	When 4000 , it is 'A'	12:L			
5	0011	Range						
6	0011	Function						
7	0011	STATE_ACDC	0000:OFF	0001:AC	0010:DC	0011:AC+DC		
8	0011	+/- □STATE_ATUO	0xxx:+	1xxx:-	x000:OFF	x001:AUTO	x010:Manual	
9	0x0D							
10	0x0A							

Function□	Range
0 AC_mV	Range 0: 400mV
1 DCV	Range 1: 4V 2:40V 3:400V 4:1000V
2 ACV	Range 1: 4V 2:40V 3:400V 4:750V
3 DC_mV	Range 0: 400mV
4 Ohm	Range 1:400 2:4k 3:40k 4:400k 5:4M 6: 40M
5 C	Range 1:40n 2:400n 3:4u 4:40u 5:400u 6: 4m 7:40m
6 □	Range 0: 1000
7 uA	Range 0:400u 1:4000u
8 mA	Range 0:40m 1:400m
9 10A	Range 0: 10
10 Fm	Range 0:
11 Diode	Range 0:
12 Hz	Range 0:40 1:400 2:4k 3:40k 4:400k 5: 4M 6:40M 7:400M
13 □	Range 0: 1832
14 □	
15 %(4-20mA)	Range 0: