

Fluke 5100B Calibrator	Fluke 15B+ Ser-Nr. 29092820WS	Specification acc. Fluke manual	from	up to
100,0 mVDC	99,0 mVDC	1,0 % + 10 Digit	98,0	102,0 mVDC
200,0 mVDC	198,0 mVDC	1,0 % + 10 Digit	197,0	203,0 mVDC
0,500 VDC	0,493 VDC	0,5 % + 3 Digit	0,495	0,506 VDC
1,000 VDC	0,986 VDC	0,5 % + 3 Digit	0,992	1,008 VDC
2,000 VDC	1,974 VDC	0,5 % + 3 Digit	1,987	2,013 VDC
3,000 VDC	2,961 VDC	0,5 % + 3 Digit	2,982	3,018 VDC
4,000 VDC	3,948 VDC	0,5 % + 3 Digit	3,977	4,023 VDC
5,00 VDC	4,93 VDC	0,5 % + 3 Digit	4,95	5,06 VDC
10,00 VDC	9,87 VDC	0,5 % + 3 Digit	9,92	10,08 VDC
15,00 VDC	14,81 VDC	0,5 % + 3 Digit	14,90	15,11 VDC
20,00 VDC	19,76 VDC	0,5 % + 3 Digit	19,87	20,13 VDC
30,00 VDC	29,64 VDC	0,5 % + 3 Digit	29,82	30,18 VDC
40,00 VDC	39,52 VDC	0,5 % + 3 Digit	39,77	40,23 VDC
50,0 VDC	49,3 VDC	0,5 % + 3 Digit	49,5	50,6 VDC
60,0 VDC	59,2 VDC	0,5 % + 3 Digit	59,4	60,6 VDC
70,0 VDC	69,1 VDC	0,5 % + 3 Digit	69,4	70,7 VDC
100,0 VDC	98,6 VDC	0,5 % + 3 Digit	99,2	100,8 VDC
150,0 VDC	148,0 VDC	0,5 % + 3 Digit	149,0	151,1 VDC
200,0 VDC	197,4 VDC	0,5 % + 3 Digit	198,7	201,3 VDC
300,0 VDC	296,1 VDC	0,5 % + 3 Digit	298,2	301,8 VDC

Fluke 5100B Calibrator, AC 50 Hz	Fluke 15B+ Ser-Nr. 29092820WS	Specification acc. Fluke manual	from	up to
100,0 mVAC	99,0 mVAC	3,0 % + 3 Digit	96,7	103,3 mVAC
200,0 mVAC	198,0 mVAC	3,0 % + 3 Digit	193,7	206,3 mVAC
0,500 VAC	0,493 VAC	1,0 % + 3 Digit	0,492	0,508 VAC
1,000 VAC	0,986 VAC	1,0 % + 3 Digit	0,987	1,013 VAC
2,000 VAC	1,973 VAC	1,0 % + 3 Digit	1,977	2,023 VAC
3,000 VAC	2,959 VAC	1,0 % + 3 Digit	2,967	3,033 VAC
4,000 VAC	3,945 VAC	1,0 % + 3 Digit	3,957	4,043 VAC
5,00 VAC	4,94 VAC	1,0 % + 3 Digit	4,92	5,08 VAC
10,00 VAC	9,87 VAC	1,0 % + 3 Digit	9,87	10,13 VAC
15,00 VAC	14,80 VAC	1,0 % + 3 Digit	14,82	15,18 VAC
20,00 VAC	19,74 VAC	1,0 % + 3 Digit	19,77	20,23 VAC
30,00 VAC	29,61 VAC	1,0 % + 3 Digit	29,67	30,33 VAC
40,00 VAC	39,48 VAC	1,0 % + 3 Digit	39,57	40,43 VAC
50,0 VAC	49,3 VAC	1,0 % + 3 Digit	49,2	50,8 VAC
100,0 VAC	98,6 VAC	1,0 % + 3 Digit	98,7	101,3 VAC
150,0 VAC	147,9 VAC	1,0 % + 3 Digit	148,2	151,8 VAC
200,0 VAC	197,3 VAC	1,0 % + 3 Digit	197,7	202,3 VAC
300,0 VAC	295,9 VAC	1,0 % + 3 Digit	296,7	303,3 VAC